III GAS DECK OVEN-SM8 SERIES

SINMAG machines



Standard panel




SM-803T/SM-803F/SM-803S



SM-803A

- Stainless steel door or glass door.
- The chamber of the oven is constructed of corrosion-resistant aluminized steel.
- The ovens are composed of detachable decks, easy to installation at site.
- Light and timer standard on each deck.
- Doors with windows open down to access baking chamber.
- Stainless steel frame, bottom-placed proofer and top-placed convection oven are options.
- Optional accessories:steam device;exhausting hood;stone plate.
- Modular design-decks can be add easily later as your operation expands.
- Easy to use digital controls for temperature, steam time, and top and bottom heat controls for each individual deck.
- Easy maintenance baking chamber.
- Casters.



| Model SI Number of Decks Number of Trays(per deck) 3 | | 1-803T | SM-803F | SM-803S | SM-803A | |
|--|---------|-----------------|----------------------------|---------|----------------|---------|
| | | 3 | | | | |
| | | 2 | 4 | 3 | 5 | 3 |
| Tray Size(mm) | 400X600 | 460X760 | 400X600 | 400X600 | 400X600 | 460X760 |
| Tray Layout | | | | | | |
| External Dimension(mm) | Width | 1490 | 1770 | 1770 | 2190 | |
| | Depth | 1150 | 1175 | 1040 | 1240 | |
| | Height | 1755 | 1755 | 1755 | 1860 | |
| Baking Chamber Dimension(mm) | Width | 1020 | 1300 | 1300 | 1720 | |
| | Depth | 805 | 840 | 650 | 845 | |
| | Height | 240 | 240 | 240 | 250 | |
| Weight(kg) | | 720 | 800 | 750 | 1340 | |
| Electric Power per Deck(kw) 0.14 | | 0.14 | 0.2 | 0.2 | 0.26 | |
| Thermal Output per Deck(kcal/h) 8600 | | 3600 | 9795 | 8600 | 12660 | |
| Temperature Rai | nge(°c) | | 0~30 | 00 | | |
| Outside Panel(front side) | | stainless steel | | | | |
| Outside Panel(other sides) | | | aluminum&zinc-coated steel | | | |