
III RETARDER/PROOFER-WITH FIXED SHELVES



Digital control panel







Features

- Single door or double door.
- The cabinet is made of stainless steel.
- -3-steps in operation: -Retard; -Recovery; -Proof
- Durable construction.
- Doors with tempered glass.
- Easy maintenance.
- Working fast and efficiently, yielding even proofing with full loads or partial loads.
- Sinmag retarder proofers are built with durable components and reliable, easy-to-use controls.
- Castors.



Model	DC-18S	DC-18F	DC-36F	DC-36SA	DC-232S	DC-236S	DC-236SZ
Capacity(number of trays) 18		18	36	36	32	36	36
Tray Size (mm)	400X600	460X720	460X720	400X600	400X600	400X600	400X600
Number of Shelve	s 18	18	18	18	16	18	18
Tray Layout							
Dimension(mm)	Width 555	760	1270	755	775	755	755
	Depth 1025	1070	1070	1280	1215	1225	1225
	Height 2215	2135	2135	2215	1950	2215	2220
Door	single door	single door	double door	single door	double door	double door	double door
Compressor Power(hp) 0.5		1.125	1.125	1.125	0.625X2	0.5X2	0.625X2
Heater Power(kw) 2		2	2.3	2.3	1.5X2 heaters	1.5X2 heaters	1.5X2 heaters
Control Mode		digital control panel			2 independent digital control panel		
Temperature Rang	ge(℃) 2~40	2~40	2~40	2~40	-10~40	2~40	-10~40
Weight(kg)	160	180	240	205	220	240	240
Outside stainless s panel with PU insu		60mm	60mm	50mm	60mm	50mm	50mm

Drawings, descriptions and photos are not contractual and can be modified.